







ABOUT MODULAR PRO LIGHTING

Having accesse to the state-of-the-art and high-quality lighting products has always been a concern for the architects and interior designers. Analyzing the similar products of the leading lighting companies in the world, Modular Pro Lighting Company has localized, designed and produced cutting-edge lighting products due to their demand in domestic market. The expert team of Modular Pro has provided a diverse variety of the latest lighting products with high-quality and reasonable price for designers and architects by processing and developing modular thinking in design, manufacturing and product installation. Having the ability to compete with similar products from overseas has made Modular Pro Lighting Company one of the main choices for designers and architects. We hope that we will be able to play a significant role both in domestic and foreign market by producing and introducing Iranian high-quality products to the world.





Modularity

Modularity is about creating one design that has multiple applications. Extending product families beyond what seems possible. Assisting, stimulating and inspiring interior designers and architects, with almost limitless options. Our fixtures and linear lighting strengthen the architecture of residential homes, hospitality venues, shops and offices. Our showrooms, sales organization and vast network of partners make us truly nominant.




Remote Control Everything!


















Magnetic(PNP)



Remote Control



Module Controler



Choosable size



Modular



Multiple Luminary



Easy installation



RGB



TW








Family Overview


Light Modules Collection

PNP Technology

Modules

Elevetion,






Light is the soul of Architecture


Create extraordinary lighting solutions that reach a new level of elegance and flexibility! The miniaturized slim light sources can be integrated perfectly into the architecture to achieve powerful but amazing aesthetic light fixtures. This rigid LED light source fits around corners and under shelves with a seamless and homogenous soft light and disappears even in the smallest coves or niches: the ideal solution for retail outlets, supermarkets, or the accentuation of showcases, corridors, and stairwells.



more than just lines of light

Since perfect lighting is of special importance in hotels and restaurants, it requires great attention. Sophisticated, well thought-out lighting concepts and LED lighting systems contribute significantly to create an atmosphere where guests feel at ease from the very first moment and enjoy their stay. It is essential that rooms can be cleverly divided into different zones enhancing privacy or relaxation while ensuring that public areas are brightly lit. Add a sophisticated look to hospitality projects with Modular pro Vanessa SD serie.







Linear Lights


Choose Your Colour Black, White

Choose your length 30cm/60cm/120cm

Choose your Power 9W/18W/36W

Various lighting options Meet your need.

Bring lighting designs for office to a new level and add value with delicate lines when it is suitable and exactly in the length required. In fact, perfect lighting is a key prerequisite for creating a working or learning atmosphere that motivates employees, customers, school pupils or students. Our State-of-the-art LED lighting in Modular Pro provides you with numerous options to present your company, school, academy or university in a perfect light – and combine decorative, colorful light accents with white light.




Invisible Dark Lights

Choose your colour Black, White

Choose the number of spots 5x, 10x, 15x


Choose your ies Lens, Reflector

Choose your Power 5W/10 W/15 W












Spot light


Choose Your Colour Black, White

Choose your mount type pendant/track

Choose Your Power 6W/12W/18W











TECHNICAL INFORMATION OVER VIEW

Intended use _

Easy to install

Set up after dry-wall installation

Fast installation

Easy to repair

Long life span


No space is needed for power supply(220V)

Easy to adjust the length without manipulating LED modul

Suitable for indoor use (IP43)

Compatible with dry-wall details


Suitable for various applications (flanged recessed/pendant and surface mounted)




- 1- Main rail (Pendant)
- 2- Tilt dark light module
- 3-Dark light module
- 4-Track light module

INSTALLATION DETAILS

Application _



Recessed Application Detail




General information _____

Applications						
Trimless recessed	Available					
Flanged recessed	Available					
Surface mounted	Available					
Pendant	Available					


Material/Surface	
Main body	Extruded alminium
Body paint	Electrostatic paint
Body colors	White/Sand Gray/Black
Diffuser	Extruded polycarbonate
Fixture	Plated steel
IP	42

	Related products								
01	Linear light module		A		A	Available			
02	Dark light module					Available			
03	Tilt light module					Available			
04	Track light module					Available			
05	Pendant light module					Available	:		

Rail information _____




Rail	Surface mounted	Flanged	Trimless	
Profile width[mm]	46	71	9 9	
Profile height[mm]	60		95	
Total height[mm]	60	61	60	
Length[mm]		Unlimited >60		
Gap width for installation[mm]		5 5		
Weight[kg/m]	1.3	1.75	1.85	



Physical properties		30 cm		60 cm	120 cm
Profile width[mm]	/ 🔥		A 1	34	
Profile height[mm]			A	37	
Weight[kg]		0.4		0.8	1.6

Electrical specifications	30 cm	60 cm	120 cm					
Power[w]	5_9	9_18	18_36					
Dimmable		Optional						
LED class		A&B						
LED circuit		Contant Current						
Working temperature		-25degree~+50degree						
Input voltage		210 ~ 265 v						
THD		<15%						
PF[%]		>0.9						
Driver type	Isolate							
Driver current[mA]	240							
Life span[hrs]		>50000						


Exposure	30 cm	60 cm	120 cm					
Lumens[Im]	650_1300	1300_2600	2600_5200					
Beam angle	120							
Mac Adam index	3							
Available temperatures[k]	3000/4000/5000							
Efficiency[lm/w]	80							
CRI	>80							



Physical properties	/ /		5x	1	0x	15x
Profile width[mm]					34	
Profile height[mm]		A			37	

Electrical specifications	5x	10x	15x			
Power[w]	5_10	10_20	15_30			
Dimmable		Optional				
LED class		A				
LED circuit		Contant Current				
Working temperature		-25degree~+50degree				
Input voltage		210 ~ 265 v				
THD		<15%				
PF[%]		>0.9				
Driver type	Isolate					
Driver current[mA]	240					
Life span[hrs]	>50000					

Exposure	5x	10x	15x					
Lumens[Im]	650_1300	1300_2600	1950_3900					
Beam angle	15°							
Mac Adam index	3							
Available temperatures[k]	3000/4000							
Efficiency[lm/w]	130							
CRI	>80							




Physical properties	5x		10x	13x
Profile width[mm]			34	
Profile height[mm]		A	110	

Electrical specifications	5x	10x	13x				
Power[w]	5_10	10_20	15_30				
Dimmable		Optional					
LED class		А					
LED circuit		Contant Current					
Working temperature		-25degree~+50degree					
Input voltage		210 ~ 265 v					
THD		<15%					
PF[%]		>0.9					
Driver type	Isolate						
Driver current[mA]	240						
Life span[hrs]	>50000						

Exposure	5x	10x	13x		
Lumens[Im]	650_1300	1300_2600	1950_3900		
Beam angle	15°				
Mac Adam index	3				
Available temperatures[k]	3000/4000				
Efficiency[lm/w]	130				
CRI	>80				


Track light module _



Physical properties	315	617	817
Diameter	27	60	80
Height[mm]	150	170	170

Electrical specifications	315		617		817
Power[w]	6		12		18
Dimmable			Optional		
LED class			В		
LED circuit			Contant Current		
Working temperature			-25degree~+50degree		
Input voltage			210∼ 265 v		
THD			<15%		
PF[%]			>0.9		
Driver type			Isolate		
Driver current[mA]	300				
Life span[hrs]	>50000				

Exposure	315	617	817			
Lumens[lm]	7 80	1560	2 340			
Beam angle		38°				
Mac Adam index	3					
Available temperatures[k]	3000/4000					
Efficiency[lm/w]	130					
CRI	>80					



Physical properties	325	625	617	810	815
Diameter	27 Ф	60 Ф	60 Ф	80 Ф	80 Ф
Height[mm]	2 50	2 50	170	100	150

Electrical specifications	325	625	617	810	815	
Power[w]	3		12		18	
Dimmable			Optional	,		
LED class			В			
LED circuit			Contant Current			
Working temperature		-25degree ~+50degree				
Input voltage	210 ~ 265 v					
THD	<15%					
PF[%]	>0.9					
Driver type	Isolate					
Driver current[mA]	300					
Life span[hrs]	>50000					

Exposure	325	625	617	810	815	
Lumens[lm]	390		2 340			
Beam angle	1 5 [°]	38°				
Mac Adam index	3					
Available temperatures[k]	3000/4000					
Efficiency[lm/w]	130					
CRI	>80					



A technical sheet is a summary of products that identifies the features, specifications, and other criteria of different lighting systems that the user will need to understand in order to choose the best option.

44 | Modular pro | Vanessa SD | Modular pro | Vanessa SD | 45





Modular prolighting

© 09374039911



let there be light Modular pro lighting

